

Click Here

























Bestway The Clean Sun Powered Pool Pad by Bestway® provides an economical and environmentally friendly way to heat swimming pool water by harnessing the energy of the sun. It is easy to set up with included adaptors compatible with 3.2 cm and 3.8 cm hoses. It is compatible with 2500 gal filter pumps and 2000 gal sand filters and below and it works with all above ground pools. The Pad uses solar power to increase swimming pool water temperatures by approximately 3 ~ 5° C (5 ~ 9° F) depending on the weather conditions. With a heating area of 1.46 square meters (15.72 square feet), it can be used in multiples to work together for different size pools. Size: 43 in. x 67 in. / 1.10 m x 1.71 m Compatible with 2,500 gal./h (9,462 L/h) filter pumps and 2,000 gal./h (7,570 L/h ) sand filters and smaller Easy set up with included adaptors compatible with 1.25 in. (3.2 cm) and 1.5 in. (3.8 cm) hoses Increase swimming pool water temperatures by approximately 5 ~ 9°F (3 ~ 5°C) depending on weather condition High-tech material provides superior resistance to weather and other abrasive agents Can be used in multiples to work together for different size pools Contents: 1 pool heating pad Share Facebook X (Twitter) Pinterest Riddle: I flow like a river, but I'm not water so clear. My touch is destructive, something to fear. I'm born from the depths, where heat is extreme. In molten embrace, a fiery dream. What am I? The answer to this riddle is: Lava Let's break down the riddle and explain why lava fits each clue: "I flow like a river, but I'm not water so clear." Lava flows like a river when it erupts from a volcano, creating streams and channels. Unlike water, lava is not clear but typically appears red, orange, or yellow. "My touch is destructive, something to fear." Lava is extremely hot and destructive. It can burn and consume everything in its path. Its destructive power is indeed something to be feared, capable of destroying buildings, forests, and entire landscapes. "I'm born from the depths, where heat is extreme." Lava originates deep within the Earth, in areas of extreme heat. It's formed when rock melts due to high temperatures and pressure in the Earth's mantle. "In molten embrace, a fiery dream." Lava is molten rock, existing in a liquid state due to intense heat. The term "fiery dream" poetically describes its nature - a surreal, flowing mass of liquid fire. This riddle effectively uses poetic language and metaphors to describe the characteristics of lava: Its flow is likened to a river, highlighting its liquid nature. Its destructive power is emphasized, setting it apart from benign flowing water. Its origin in the Earth's depths and its molten, fiery nature are vividly portrayed. The riddle cleverly plays on the contrast between lava and water - both flow, but their natures and effects are drastically different. Flowclear Outdoor Shower (9 Gal) - Product Video (2)Bestway L&G Image not available forColor: To view this video download Flash Player Shop the store on Amazon › ENPTESDEFINLITFRELRUPLHUSVWE SUGGEST NOT TO RETURN THE PRODUCT TO THE STOREQUESTIONS? PROBLEMS?MISSING PARTS?For FAQ, Manuals, Videos OrSpare Parts, Please Visitbestwaycorp.com/supportVisitwww.bestwaycorp.com/supportforhelp58499 Hmax 1.5 mOWNER'S MANUALbestwaycorp.com/supportVisit Bestway YouTube channel Page 22EN• Always unplug this product from the electrical outlet before removing. • CAUTION: Read the instruction before using the appliance and CAUTION: This sand filter is for use with storable pools only. Do not • This appliance is not intended for use by persons (including children) experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible • It is necessary to have the plug accessible after installation of the pool. WE SUGGEST NOT TO RETURN THE PRODUCT TO THE STOREQUESTIONS? PROBLEMS?MISSING PARTS?For FAQ, Manuals, Videos OrSpare Parts, Please Visitbestwaycorp.com/supportforhelp Page 3Page 4Page 5Page 66accdueantly falling. Fully assembled sand filter will exceed spaced 86 mm apart. Use two bolts and nuts with a maximum NOTE: Use only special pool-grade filter sand, free of all limestone IMPORTANT: We suggest using #20 silica sand with your pool sand NOTE: To avoid damaging the Skimmer when adding sand, pour NOTE: Use 28 g (0.06 lbs) Flowclear™ Polysphere to replace REF.NO SPARE PART NO. A B1 1 12 1 13 2 24 1 15 1 16 1 17 1 18 1 19 1 110 1 111 1 112 5 513 1 114 1 115 8 816 1 117 2 018 2 019 1 120 1 121 1 122 1 123 1 124 2 21 01 025P03850P61138ASS16P03832P61209ASS16P03833P03834P61211ASS16P6581ASS16P6580ASS16P03835P6614ASS16P6029ASS16P03830P61214ASS16P61210ASS16P03829P6916ASS16P6124ASS16P6561ASS16P6562ASS16P6563ASS16P03851(EU)/P005777(GB)/P03840P6518ASS16P61322ASS16P61318ASS16AX2BAB25P61322ASS16P61318ASS16 Page 7Page 8Page 99STOPDBA2231DGarden hose (not included)For Drain, Backwash, Rinse functionP61318ASS16P61322ASS16BAP6916ASS16 Page 10Page 1111Valve set to the Closed function or it will seriously damage the To avoid water leakage, screw the Port D Cap onto the Control Valve BCACBACBADCBACBDACBA Page 12Page 131.605101520231.41.210.80.60.40.20psibarCAUTION: You must ensure the sand filter is switched off and unplugged before any maintenance begins or severe risk of injury or death exists. As dirt builds up in the sand filter, the pressure reading on Pressure Gauge will increase. When the Pressure Gauge is 0.56 Bar (8.0 PSI) or higher, or water flow to the pool is too low, it is time to clean the sand. To clean the sand bed, follow all instructions outlined previously in : Backwash and Rinsing.1. Switch off the sand filter and set the Control Valve to the Closed function.2. Close the connection valves.3. Remove the Strainer Cover by unscrewing it.4. Take out the Strainer, remove any debris.5. Put the Strainer back into position. Ensure the hole in the strainer is aligned.6. Ensure the Seal Ring is in place. Secure the Strainer Cover back.7. Open the connection valves.NOTE: The Strainer must be emptied and cleaned periodically. A dirty or blocked strainer will reduce the performance of the sand filter.1. Switch off the sand filter and set Control Valve to the Drain function.2. Detach the Hose from the connection valve's Port A and sand NOTE: 1. The Pressure Gauge is just used for measuring the water pressure, not used for precision measurement.2. We recommend you clean the sand bed once a month or less regularly depending on how often the pool is used. Do not clean the sand too frequently. CLEANING THE STRAINER13 SAND FILTER MAINTENANCE LOWERING OR DRAINING POOL WATERPage 14Page 1515PT• Quando o aparelho não for utilizado durante um longo período de tempo, como • CUIDADO: leia as instruções antes de utilizar o aparelho e a cada CUIDADO: Esta bomba deve ser usada somente para piscina desmontáveis. • Este equipamento pode ser usado por crianças de 8 anos de idade e superior e que o filtro de areia está a pelo menos 2 metros afastado da piscina.Mantenha Nunca coloque o filtro de areia em uma área que possa acumular água ou que Recomenda-se um período mínimo diário de filtração de 8 horas, para garantir também de acordo com os regulamentos/legislação aplicáveis. Preste atenção RECOMENDAMOS NÃO DEVOLVERO PRODUTO PARA A LOJA Dúvidas? Problemas?Faltam peças?Para FAQ, manuais, vídeos oupeças de reposição, visitebestwaycorp.com/supportSeprecisadeajuda.visitewww.bestwaycorp.com/support Page 1616que o filtro de areia está a pelo menos 2 metros afastado da piscina.Mantenha Nunca coloque o filtro de areia em uma área que possa acumular água ou que Recomenda-se um período mínimo diário de filtração de 8 horas, para garantir também de acordo com os regulamentos/legislação aplicáveis. Preste atenção Page 17Page 18Page 191. 193. O padrão de TESTE EN60335-2-41 exige que o filtro de areia seja filtro de areia. Totalmente montado o filtro de areia tem mais de COLOQUE A AREIA DE FILTRO PARA PISCINA/POLI ESFERAS FLOWCLEAR™ NOTA: Use somente areia para filtros especiais para piscinas, sem areia, o desempenho de filtragem será reduzido e o filtro de areia pode ficar IMPORTANTE. Sugerimos o uso da areia de sílica nº 20 com o filtro de Alguns pequenos detritos podem passar para a areia e retornar à piscina. Isso Também sugerimos entrar em contato com o revendedor da piscina para obter o produto químico feito especificamente para limpar a areia. A NOTA: Para evitar danificar a escumagem ao adicionar a areia, coloque NOTA: A areia/poli esferas Flowclear™ não estão incluídas.NOTA: Utilize 28 g de poli esferas Flowclear™ para substituir 1 kg de REF.NR.PECA SOBRESSALENTE NRA B1 1 12 1 13 2 24 1 15 1 16 1 17 1 18 1 19 1 110 1 111 1 112 5 513 1 114 1 115 8 816 1 117 2 018 2 019 1 120 1 121 1 122 1 123 1 124 2 21 01 025P03850P61138ASS16P03832P61209ASS16P03833P03834P61211ASS16P6581ASS16P6580ASS16P03835P6614ASS16P6029ASS16P03830P61214ASS16P61210ASS16P03829P6916ASS16P6124ASS16P6561ASS16P6562ASS16P6563ASS16P03851(EU)/P005777(GB)/P03840P6518ASS16P61322ASS16P61318ASS16AX2BAB25P61322ASS16P61318ASS16 Page 20Page 21Page 2222PAREDBA2231Mangueira de jardim (não incluída)Para função de Drenagem, Retrolavagem, e de EnxugamentoDP61318ASS16P61322ASS16BAP6916ASS16 Page 23Page 24Page 25251. Pressione para baixo no manipulo da Válvula de Controle e rode para a função Retrolavagem.4. Ligue o filtro de areia e opere o filtro de areia durante 1 min. Isto circula água para trás através Page 26

- <http://infovagas.com/userfiles/file/46694d8c-9cd3-4cfd-bd68-adf51dce4543.pdf>
- <http://webbuilders.com/files/file/b117157e-10a8-45fb-a24e-1e69a091515c.pdf>
- bamixabe
- mosege
- <http://aranykoronakft.hu/userfiles/file/52b8824e-cf3f-494d-bbca-8440484e1be6.pdf>